

PRO AUDIO TWEETERS











PRO AUDIO MIDRANGE



	BLACKAIRPRO6M-V0	BLACKAIRPRO8M-V0
ä	Pro midrange	Pro midrange
ı	1-way	1-way
ı	Size : 6.5" (165mm)	Size: 8.2" (208mm)
ı	480W / 160W	540W / 180W
ı	Freq:125Hz-10.5kHz	Freq:100Hz-10.5kHz
	4Ω	4Ω
ı	MT Depth : 72mm	MT Depth : 85mm
1	MT Dia: 141mm	MT Dia: 183mm











3D12D1SPL-V4	BD12D2SPL-V4	BD15D1SPL-V4	BD15D2SPL-V4
Size : 12"	Size : 12"	Size : 15"	Size : 15"
9000W / 3000W	9000W / 3000W	9000W / 3000W	9000W / 3000W
15Hz - 850Hz	15Hz - 850Hz	15Hz - 850Hz	15Hz - 850Hz
Dual 1Ω	Dual 2Ω	Dual 1Ω	Dual 2Ω
Coil: 3" 8 layer	Coil: 3" 8 layer	Coil : 3" 8 layer	Coil : 3" 8 layer
Depth: 285mm	Depth : 285mm	Depth : 300mm	Depth: 300mm
Dia : 301mm	Dia : 301mm	Dia : 375mm	Dia : 375mm
3ox : 3 - ∞ft3	Box : 3 - ∞ft3	Box : 3 - ∞ft3	Box : 3 - ∞ft3



SUBWOOFERS







	Appen 1	Mark C
ХД Х	POWERBOX800.1D-V3	POWERBOX1200.1D-V3
н	Monoblock	Monoblock
23	2.2" x 5.9" x 11.2"	2.2" x 5.9" x 12.8"
_	370 watts 4Ω	500 watts 4Ω
- 2	600 watts 2Ω	800 watts 2Ω
3	800 watts 1Ω	1200 watts 1Ω
	1600 watts MAX	2400 watts MAX
	Freq : 20Hz - 250Hz	Freq: 20Hz - 250Hz
ΠL	Class D	Class D



	ਅਕਵ
	POWERBOX250.2-V0
н	2 channel
23	2" x 13.8" x 7.6"
_	2 x 250 watts 4Ω
	2 x 350 watts 2Ω
3	1 x 700 watts 4Ω
_	1400 watts MAX
	Freq: 30Hz - 30kHz
L	Class AB

√ vibeaudio.co.uk

f vibeaudio

CAR AUDIO

0 vibeaudio

wibeaudio 👑

COAXIAL







	all of the second	oral oral oral oral oral oral oral oral			
	SLICK4-V7	SLICK5-V7	SLICK57-V7	SLICK6-V7	SLICK693-V7
J.	coaxial	coaxial	coaxial	coaxial	coaxial
	2-way	2-way	2-way	2-way	3-way
U	size : 4"	size : 5.25"	size: 5.25" x 7.5"	size : 6.5"	size : 6" x 9"
•	150w / 50w	210w / 70w	240w / 80w	240w / 80w	480w / 160w
	66hz-25khz	60hz-25khz	54hz-25khz	54hz-25khz	50hz-25khz
J	4 ohms	4 ohms	4 ohms	4 ohms	4 ohms
L	depth: 41mm	depth: 46mm	depth : 53mm	depth : 61mm	depth: 76mm
	dia : 94mm	dia : 112mm	127 x 180mm	dia: 142mm	44 x 216mm







BA1TW-V4	BA3M-V4	BA6MW-V4	BLACKAIR6
Component	Component	Component	Component
1-way	1-way	1-way	2-way
Size : 2"	Size : 3"	Size : 6.5"	Size : 6.5"
180W / 60W	180W / 60W	420W / 140W	420W / 140W
2.5kHz - 20kHz	300Hz - 20kHz	45Hz - 25kHz	45Hz - 25kHz
4Ω	4Ω	4Ω	4Ω
Depth: 43mm	Depth: 43mm	Depth : 65mm	Depth : 65mr
Dia: 75mm	Dia: 75mm	Dia : 143mm	Dia: 143mm



SLICK1-V7 Tweeter	SLICK6C-V7	SLICK6SQC-V9
Tweeter	Component	Component
1-way	2-way	2-way
1-way Size : 2"	Size : 6.5"	Size : 6.5"
150W / 50W	270W / 90W	300W / 100W
1.5kHz - 25kHz	54Hz - 25kHz	54Hz - 25kHz
-4Ω	4Ω	4Ω
Depth: 13mm	Depth : 61mm	Depth : 61mm
MT Dia : 38mm	MT Dia: 142mm	MT Dia: 142mm
2.4 . 00	, mr Diai r izmin	in sair isini









	(Vise)	Vise	Vier	VIDE
Je V	SLICK8D2-V3	SLICK10D2-V3	SLICK12D2-V3	SLICK12D4-V3
J.	Size: 8"	Size : 10"	Size : 12"	Size : 12"
	1350W / 450W	1500W / 500W	1500W / 500W	1500W / 500W
U	35Hz - 1.5kHz	30Hz - 1kHz	25Hz - 850Hz	25Hz - 850Hz
•	Dual 2Ω	Dual 2Ω	Dual 2Ω	Dual 4Ω
The state of the s	Coil: 2" 4 layer	Coil: 2" 4 layer	Coil: 2" 4 layer	Coil: 2" 4 layer
E P	Depth: 120mm	Depth: 138mm	Depth: 147mm	Depth: 147mm
- Line	Dia : 181mm	Dia : 230mm	Dia : 277mm	Dia : 277mm
7	Box : 0.5 - 1ft3	Box : 1 - 2ft3	Box: 1.5 - 2.5ft3	Box: 1.5 - 2.5ft3



(Variation of the Control of the Con	VIET
PULSE10D2-V3	PULSE12D2-V3
Size : 10"	Size : 12"
1050W / 350W	1050W / 350W
Freq: 30Hz - 1kHz	Freq: 25Hz - 850Hz
Dual 2Ω	Dual 2Ω
Coil : 2" 4 layer	Coil : 2" 4 layer
MT Depth : 133mm	MT Depth : 142mm
MT Dia: 230mm	MT Dia: 277mm
Bov : 1 - 2ft3	Boy : 1.5 - 2.5ft3

AMPLIFIERS



	Q ns - msm - storement	**** * : *** **** **** * **** * ***** * ******	0
yox X	POWERBOX65.4-8MDSP-V3	POWERBOX80.6-8DSP-V3	POWERBOX80.8-10DSP-V3
⊡	4 channel with 8 Channel DSP	6 channel with 8 Channel DSP	8 channel with 10 Channel DSP
	1.5" x 7.4" x 3.2"	1.8" x 10.6" x 7.2"	1.8" x 7.2" x 7.2"
_	4 x 65 watts 4Ω	6 x 80 watts 4Ω	8 x 80 watts 4Ω
	n/a	6 x 100 watts 2Ω	8 x 100 watts 2Ω
3	n/a	4 x 80 + 1 x 200 watts 4Ω	6 x 80 + 1 x 200 watts 4Ω
ō	520 watts max	1200 watts MAX	1600 watts MAX
ī	20hz - 20khz	Freq: 20Hz - 20kHz	Freq: 20Hz - 20kHz
'-	Class D	Class D	Class D




And 1 and Annual Antonia Anguson		(1864 - 185 Rec.) Ro. Sec. Lance
POWERBOX80.4M-V0	POWERBOX100.4M-V0	POWERBOX150.4M-V0
4 channel	4 channel	4 channel
1.9" x 9.1" x 5.3"	1.9" x 9.1" x 5.3"	1.9" x 15.4" x 5.3"
4 x 80 watts 4Ω	4 x 100 watts 4Ω	4 x 150 watts 4Ω
4 x 120 watts 2Ω	4 x 120 watts 2Ω	4 x 240 watts 2Ω
2 x 240 watts BR	2 x 240 watts BR	2 x 480 watts BR
960 watts MAX	960 watts MAX	1920 watts MAX
Freq: 10Hz - 30kHz	Freq: 10Hz - 30kHz	Freq: 10Hz - 30kHz
Mini Class D	Mini Class D	Mini Class D



×	POWERBOX400.1M-V7	POWERBOX65.4M-V7
XDG	monoblock	4 channel
1	1.5" x 6.2" x 3.2"	1.5" x 7.4" x 3.2"
	170 watts 4Ω	4 x 65 watts 4Ω
	250 watts 2Ω	n/a
	400 watts 1Ω	n/a
	800 watts max	520 watts max
1	10hz - 500hz	20hz - 20khz
1	Class D	Class D









ette.		
	Model	CLAWK
	Power Cable Length	5M
	Ground Cable Length	1M
	Input Cable Length	5M
	Speaker Cable Length	2 x 5M
	Speaker Cable Dia.	16AWG
	Power / Ground Cable Dia.	10 AW0
	Supplied Fuse Rating	30 Am






Model	VSAWK8-V1
Power Cable Length	5M
Ground Cable Length	1M
Input Cable Length	5M
Speaker Cable Length	2 x 5M
Speaker Cable Dia.	16AWG
Power / Ground Cable Dia.	8AWG
Supplied Fuse Pating	60 Amp ANII







ENCLOSURES

UNDERSEAT







v	SLICKC10A-V0
•	Size : 10"
ì	Active enclosure
,	540W / 180W
	4Ω
	2.9" x 10.2" x 13.6"
	Acoustic suspension
	Slim Fit
	Mono amp









v	SLICKC10A-V0
J.	Size : 10"
	Active enclosure
U	540W / 180W
•	4Ω
	2.9" x 10.2" x 13.6"
_	Acoustic suspension
L	Slim Fit
7	Mono amp





BA10SQ-V4	BA10ASQ-V4
Size : 10"	Size : 10"
Passive enclosure	Active enclosure
900W / 300W	900W / 300W
Dual 2Ω	Dual 2Ω
5" x 12.4" x 17.8"	5" x 12.4" x 17.8"
Acoustic suspension	Acoustic suspension
Compact	Compact
N/A	POWERBOX400.1M-V7

COMPACT

ENCLOSURES





PERFORMANCE ENCLOSURES





SLICKMIT8-V3	SLICKMIT10-V3
slick 8	slick 10
passive enclosure	passive enclosure
1350w / 450w	1500w / 500w
dual 2 ohms	dual 2ohms
12.8" x 10.6" x 14.6"	15" x 13.4" x 16.1"
4th order bass reflex	4th order bass reflex
Trapezius	Trapezius
Quad post terminal	Quad post terminal



PRO ENCLOSURES







	(visco) (visco)
SLICKMIT12-V3	SLICKMIT12T-V3
SLICK 12	2 x SLICK 12
Passive enclosure	Twin passive
1500W / 500W	3000W / 1000W
Dual 2Ω	Dual 2Ω
17.5" x 17.5" x 18.1"	17.5" x 29.9" x 18.1
4th order bass reflex	4th order bass reflex
Trapezius	Trapezius






SLICKPROBOX6-V0
4x SLICKPRO6M + 2x SLICKPRO37T
Full range pro audio enclosure
1950W / 650W
Stereo 2Ω
7.2" x 34.1" x 7.2"
4th order bass reflex
Trapezius Enclosure

BASS **ENCLOSURE**

√ vibeaudio.co.uk

f vibeaudio

SQ CAR AUDIO





CVEN GOLD



The CVEN SQ Speakers are engineered, designed and expertly hand built to exacting standards in England from European parts .

The open chamber tweeter has been created with unique geometery of the Silk diaphragm and a powerful Neodymium motor system to deliver an extremely wide frequency range, reaching as high as 25KHz and as low as 500Hz.

The Neodymium powered SQ Midrange, which also exceeds the parameters of most midrange drivers, to reproduce frequencies beyond the physical restraints of its com-pact size. The 65mm driver features a composite paper cone with additional

These two parts allow for revolutionary vocal and high frequency detail, and due to the

The woofer boasts an ultra-lightweight woven fibre woofer cone material which delivers enough rigidity to execute the smoothest of bass responses whilst being dexterous enough to support the transients of the mids and highs of the tweeters. A cast alloy torsion chassis houses the moving parts of the woofer and supports the powerful motor. With hand picked and matched magnets, the woofer is able to to deliver the most linear





		CVEN1SQT-V9
er	Component Midrange	Component Tw

Model	CVEN6.5SQW-V9	CVEN2.5SQM-V9	CVEN1SQT-V9
Type	Component Woofer	Component Midrange	Component Tweeter
Configuration	1-way	1-way	1-way
Speaker Size	6.5" (165mm)	2.5" (65mm)	2.5" (65mm)
Peak/RMS Power	300W/150W	160W/80W	160W/80W
Sensitivity	90dB	85dB	95dB
Frequency Response	50Hz -6kHz	150Hz -20kHz	1kHz -25kHz
Impedance	4Ω	4Ω	4Ω
Mounting Depth	3.6" (91mm)	1.5" (37mm)	1" (26mm)
Mounting Diameter	5.8" (147mm)	2" (51mm)	1.9" (47mm)
Grille Included	No	Yes	Yes

CVEN SILVER



The CVEN SQ Speakers epitomize meticulous craftsmanship, originating in England and featuring premium European components. Crafted by hand to exacting standards, they promise an unparalleled audio experience, characterized by exceptional vocal clarity and intricate high-frequency detail.

At the heart of these speakers lies the high-end tweeter, meticulously constructed with exceptional materials. This design choice ensures not only sufficient rigidity for delivering smooth high-frequency responses but also facilitates a linear frequency response for flawless sound output. Housed within a cast alloy torsion chassis, the woofer's moving components are bolstered with robustness, enabling the speaker to maintain its integrity were under demanding conditions. its integrity even under demanding cond

Furthermore, the woofer is meticulously assembled, ensuring a remarkably smooth frequency roll-off to the midrange and tweeter. This meticulous attention to detail results in sound reproduction that remains faithful to the original source, capturing every subtle nuance and delivering an immersive listening experience that exceeds



Model	CVEN6SW-V4	CVEN3SM-V4	CVEN1ST-V4
Type	Component Woofer	Component Midrange	Component Tweete
Configuration	1-way	1-way	1-way
Speaker Size	6.5" (165mm)	2.5" (65mm)	2.5" (65mm)
Peak/RMS Power	300W/150W	160W/80W	160W/80W
Sensitivity	90dB	85dB	95dB
equency Response	50Hz -6kHz	150Hz -20kHz	1kHz -25kHz
Impedance	4Ω	4Ω	4Ω
Mounting Depth	3.6" (91mm)	1.5" (37mm)	1" (26mm)
Mounting Diameter	5.8" (143mm)	2" (51mm)	1.9" (47mm)
Grille Included	No	Yes	Yes



The delivery and replication of music just as the artist intended you to hear it.

The VIBE CVEN range was created to do just that. The EISA award winning speakers were designed and engineered in the UK to deliver exquisite sound reproduction, at the most refined level.

A precision built speaker range perfectly combining midrange drivers and wideband tweeters for a harmonic sound.

The mid-woofer cone was developed to give added depth to the low bass notes, while delivering midrange up to the point of a seamless transition with the

The woofer and tweeter have complimantary frequency response curves, with the midrange having a bump at the upper midrange band and the tweeter having

The tweeter was designed in such a way that it can play extremely low, thus allowing a better sound stage when installed. When paired in a two way set up the marriage of the tweeter and mid is such that a crossover is not even required, just a high quality Mudorf capacitor for













Our R&D team have extensive experience of what makes a great DSP. Using our own hands on approach to DSP development we soon exhausted every product available from vendors across the globe and set about developing our own product from the ground

Our initial starting point was simple, create a user interface that was intuitive with an extensive options list. To not only help the novice installer build their skills, but also include enough options to

satisfy the experts. A single user interface and DSP design which could be added to a full catalogue of products.

need only learn and understand one platform across a number of products. We are proud to release this new DSP design which

Our new software is available on android and IOS and has been

developed to use with hand held devices such as phones and tablets. The wireless connection aids in vehicle tuning and the wireless connectivity gives music streaming options as standard.

AMPLIFIERS



To power our EISA award winning SQ speakers we need premium amplification.

To ensure beautiful sound, we need to ensure no colouration to the speaker with pure amplification, with class AB topology, high S/N ratio, low distortion and full range crossovers giving full control of all the speakers.

Front entry for cables for neat installation, as well as our unique heatsink where we have added all amp controls to the top panel for easy and sleek adjustment.

Model CVENS4SQ-V4

SUBWOOFER



Designed and engineered to work in harmony with our EISA award winning speakers.

This unique design is unlike anything we have ever made in our 30 year history. This woofer sounds simply beautiful.

Incredible properties such as CONEX spiders and Aluminium cone help deliver the precise bass reproduction.



Model	CVEN10SW-
Speaker Size	10.25" (260m
Peak/RMS Power	800W/400W
Sensitivity	84dB
Frequency Response	25Hz - 1.5kH
Impedance	4Ω
Voice Coil	2" 4 layer
Mounting Depth	5.8" (148mm)
Mounting Diameter	8.9" (227mm)
Enclosure Volume	0.75 - 1.5ft ³

The CVEN 12PR is hand built in the UK by our master craftsmen, and we've spared no expense on the construction. The exterior is not only clad with real Granite baffles but also luxury automotive Technosuede to cover the sides of the wooden cabinet.

The weight of the enclosure, combined with machined Aluminium mounting feet and Velcro pads, ensure that the CVEN 12PR will stay firmly in place when installed in the vehicle and prevent the enclosure from bouncing about.

This enclosure is perfectly sized for the Audiophile CVEN 10 reference subwoofer and we've added a 12 inch passive radiator which delivers increased volume and depth, without

the need to increase the cabinet size. The passive radiator also features a Steel mesh grille to offer protection when placing items in the luggage compartment.

The CVEN 12PR isn't just good, it's very good indeed.




Model	CVEN12PR-V3	
Driver	CVEN10SW	
Type	Passive enclosure	
Peak/RMS Power	800W/400W	
Impedance	4Ω	
Dimensions (H x W x D)	8.3" x 21.7" x 14.2"	
Dimensions (H x w x D)	(211mm x 550mm x 360mm)	
Configuration	4th order Passive radiator	
Enclosure Type	Passive radiator bass enclosure	














	Model	ANTIVIBESDBP-V6	ANTIVIBESD25-V3	AVSD2-V1	AVSDR-V1
	Thickness	2.5mm	1.8mm	1.8mm	1.8mm
	Construction	Butyl	Butyl	Butyl	Butyl
	Size	10.6" x 14.6" (270mm x 370mm)	10" x 10" (250mm x 250mm)	10" x 10" (250mm x 250mm)	18" x 32" (450mm x 810mm)
	Weight	3.75kg / sq.m	3.75kg / sq.m	3.75kg / sq.m	3.75kg / sq.m
	Pack qty	35 sheets	25pcs	2pcs	Roll



	Model	ANTIVIBESD-V6BP	ANTIVIBESDA-V9
and the second second	Type	1.4" (35mm)	Combo pack
//////////////////////////////////////	Sound deadening	Polyurethane	4pcs 10.6" x 14.6" (270mm x 370)
//////////////////////////////////////	Sound absorber	19.7" (500mm) x 23.6" (600mm)	2pcs 19.7" (500mm) x 23.6" (600r
	Pack qty	4 sheets	6 sheets
HIHHHHHHH	_		